

A WINDOW BEYOND LIMITS

SOLEAL NEXT The Universal Window

➤ High Performance & Sustainable



By  Hydro





SOLEAL NEXT

/ THE UNIVERSAL WINDOW

A WINDOW BEYOND LIMITS FOR THE ARCHITECTURAL CREATIVITY

MORE POSSIBILITIES

The SOLEAL Next window was created to offer architects and consultants an extensive range of solutions, giving them as much creative freedom as possible when designing a building.

More applications

SOLEAL Next is available in Visible and Minimal design with open-in and open-out functionality to adapt to all types of architectural styles. There are multiple applications: 1 and 2-vent windows and patio windows, continuous horizontal windows, integrated or overlapping assemblies, fixed-light frames, with overpanel or side fixed lights, horizontal and vertical pivot frame and top-hung frame. Most of these applications are available in both 65mm and 75mm frames.

Residential doors are also offered with low-threshold options for increased accessibility. The installation and cladding housing are the same as for our other platform products, SOLEAL Next doors.

More comfort

SOLEAL Next offers effective thermal, acoustic and weather tightness performances, complying with most international regulatory requirements. Ventilation and micro-ventilation are also available as optional solutions.

More design

SOLEAL Next combines aesthetic design with a large choice of colours and accessories, as well as concealed elements, bringing elegance and modernity to new or renovated building projects.

LESS IMPACT

Using the UN Sustainability Goals as our compass, we aim to reduce by half our CO₂ emissions by 2025 and commit to contribute to quality education and capacity building for 500,000 people in our communities and for business partners from 2018 until the end of 2030.

Lower CO₂ footprint


Using Hydro CIRCAL®, an alloy made with a minimum of 75% recycled end-of-life aluminium (post-consumer scrap), allows tons of scrap that would otherwise become solid waste to be reintroduced into the system. SOLEAL Next's thermal break elements are made from recycled material.

More recyclable

SOLEAL Next is under certification to obtain Cradle to Cradle® label. The specific characteristics contribute to constructing sustainable buildings that are eligible to be awarded to the main environmental certifications.

SOLEAL NEXT 65 & 75

/ MORE POSSIBILITIES. LESS IMPACT.



KEY FEATURES & INNOVATIONS

MORE DESIGN & AESTHETICS

- Wide choice of minimal and visible vents and frame design
- Concealed hardware
- Concealed handles and drainage
- EXCLUSIVE® handle collection

LARGE DIMENSIONS

- Module: 65 and 75 mm
- Height: up to 3 meters
- Glazing thickness: up to 69 mm
- Vent weight: up to 160 kg

MORE APPLICATIONS

- Numerous opening possibilities
- Integration with facades and other product ranges
- Composite assemblies
- Horizontal and vertical pivot frame
- Residential door
- Patio Window
- Juliet Guarding
- Motorisation available
- Magnetic window contact
- Wireless window contact

MORE SAFETY AND ACCESSIBILITY

- Burglary resistance up to RC3 and PAS24
- Security glazing beads for glass pane installation from the outside, including open-out
- Magnetic window contact: certified for high-end security
- Building management system: concealed locking sensor
- Antibacterial coating on handles on demand
- Reduced threshold for accessibility: 15-20 mm

MORE PERFORMANCES

- Thermal: U_w up to 0.79 W/m²K
- Air permeability: Class 4 (600pa)
- Watertightness:
 - Up to 1500 Pa for open-in
 - Up to 1800 Pa for open-out
- Wind pressure resistance: Class 4 / 5
- Acoustic performance: R_w up to 48 dB

MORE SUSTAINABILITY

- SOLEAL Next is made with Hydro CIRCAL®, aluminium made with a minimum of 75% recycled end-of-life aluminium.
- PVC-free components
- Cradle to Cradle®: under certification
- Dynamic EPD available on TechDesign
- 75% recycled and 95% recyclable

SOFTWARE



- Available in TechDesign
- BIM: available in Tech3D, Archicad and REVIT
- TechAcoustic

SOLEAL NEXT

/ A MODULAR SOLUTION

MINIMAL



The fine lines of the Minimal vent contribute to creating elegant and minimalistic architecture.



SOLEAL NEXT Minimal

MINIMAL CLIP-ON TRIM

The clip-on-trim adds modernity to the window and discreetly highlights the presence of the opening vent.





SOLEAL NEXT Minimal Clip-On-Trim

SOLEAL NEXT

/ A MODULAR SOLUTION

VISIBLE OPEN-IN



The visible structure is balanced between the fixed frame and the opening vent, providing an additional aesthetic touch to the window.



SOLEAL NEXT Visible Open-In

VISIBLE OPEN-OUT

Not only are there several designs of visible vents, it's also available for outward opening, giving a wide choice of possibilities.



SOLEAL NEXT Visible Open-Out

SOLEAL NEXT

/ MINIMAL


With a range of 5 different frames and 4 different vent designs, SOLEAL Next Minimal can be offered in 20 different visual aspects.

FRAME DESIGNS


- Standard
- Step
- Slope
- Concealed drainage
- T frame with concealed drainage

VENT DESIGNS


- Square
- Step
- Slope
- Clip on trim




SOLEAL NEXT 75 Minimal
Slope frame and Slope vent



SOLEAL NEXT 75 Minimal
Concealed drainage frame and Square vent




SOLEAL NEXT 75 Minimal
Step frame and Square vent



SOLEAL NEXT 75 Minimal Clip-On-Trim
Step frame and Square vent

The patented minimalist opening frame with slim, subtle sightlines is perfect to reduce the visible aluminium and to increase the amount of glazing.



SOLEAL NEXT

/ VISIBLE OPEN-IN


With a range of 5 different frames and 5 different vent designs, SOLEAL Next Visible can be offered in 25 different visual aspects.

FRAME DESIGNS


- Standard
- Step
- Slope
- Concealed drainage
- T frame with concealed drainage

VENT DESIGNS


- Square
- Step
- Slope
- Soft
- Flush




SOLEAL NEXT 75 Visible
Concealed drainage frame and Square vent



SOLEAL NEXT 75 Visible
Slope frame and Slope vent




SOLEAL NEXT 75 Visible
Standard frame and Step vent




SOLEAL NEXT 75 Visible
Standard frame and Soft vent

The stylish visible opening frame provides a contemporary, modern aesthetic.



SOLEAL NEXT

/ VISIBLE OPEN-OUT





WINDOW FEATURES

- Vent optimised for friction stay (No packer on the vent)
- Straight cut central gasket (Overlapping lips)
- Available in single and double vent
- PAS24 available

RESIDENTIAL DOOR FEATURES

- Door lock offer
- Door hinges tested at 200 000 cycles





SOLEAL NEXT

/ CONCEALED ELEMENTS AND HARDWARE

AESTHETICS

- Invisible hinges create a minimalistic look
- Slim hardware components, with harmonious finishes
- Finishing covers tie rod and frame groove for a clean appearance

FAST ASSEMBLY

- Front mounted elements
- Direct punching of the tie rod
- No groove notching on the vent
- Positioning with breakable stoppers

SIMPLE SUPPLY



- No coated or anodized part, which reduces lead time for supply
- All components are common except for the bottom hinge, which enables stock to be built up according to weight and opening

LARGE DIMENSIONS

- Up to 3 m height
- 160 kg per vent

COMPREHENSIVE SOLUTION

- Bottom hinges adapted to the vent weight and the type of project:



CONCEALED HANDLES


The window handle is hidden in the vent, adding to the harmonious appearance of the window. This innovative design idea was awarded prizes from the international expert juries of the iF DESIGN AWARD, the Red Dot Design Award. This feature is available for use on the Minimal vent.



CONCEALED DRAINAGE

Concealed, our drainage is strategically placed on the casement frame to drain water out while preventing the air from coming inside.

If in place on the visible frame, our minimalistic drainage cap features standard colour, or lacquered in order to match the tint of the window.



Concealed drainage versus traditional drainage through the frame profile and drainage caps




Architect: Elding Oscarsson Architects
Photographer: Erik Wik

SOLEAL NEXT

/ MORE AESTHETIC FEATURES

2 VENTS MULLION SOLUTIONS




REDUCED EXTERNAL SIGHTLINE


- 146 mm for Visible vent with central mullion
- 126 mm for Visible vent with reduced central mullion
- 66 mm for Minimal vent

CENTERED HANDLE

- Contributes to an harmonious internal design
- Available in Minimal and Visible vent




SOLEAL NEXT Minimal
centered handle




SOLEAL NEXT Visible
centered handle


COMPOSITE FRAME WITH OPEN-IN VENT



Minimal



Minimal Clip-On-Trim



Visible Open-In



Architect: archi Cuanctics Creatives – Diego Soroa / LKS Ingeniería – Mikel Txintxurreta, Iñone Asuery Patxi Larozgoitia
Photographer: Wenzel

SOLEAL NEXT

/ EXCLUSIVE® HANDLES COLLECTION


The discreet but effective design approach for our new EXCLUSIVE® range - SELECTION, TEMPTATION & PASSION - aims to allow users to customise their handles, creating a sophisticated but timeless and functional visual signature on SOLEAL Next windows. Our handles offer a wide choice of colours, high-quality materials and clean lines.

**PATENTED
INNOVATION**

By
TECHNAL

/ SELECTION

True to TECHNAL's practical approach to design, this range of handles draws attention with its understated and elegant lines. A strong visual identity with simple and graphic geometric shapes, round or square, with an ergonomic design to the touch that modernises the current offer. Proven quality, with anodised or coated finishes for each handle, not to mention the new black anodised finish that adds an extra level of sophistication.



/ TEMPTATION

This range builds on TECHNAL's expertise, taking its extruded aluminium design to new levels of high quality and clean lines. All the elements come in a mix of finishes, textures and colours and can be combined to get unique and personalised colour options. All this designed to achieve a unique visual sensation and a magnificent experience to the touch.




/ PASSION

Taking design to new heights, the passion range is a new expression in luxury fittings, with exclusive mixes of finishes and materials aimed at pleasing even the most demanding users. Making use of simple geometric shapes, this collection works as the perfect complement to a wide range of architectural aesthetics.



ROUND AND
SQUARED HANDLES
WITH STANDARD ROSETTES



LOCKABLE
HANDLES





SOLEAL NEXT 75
Minimal Open-In



SOLEAL NEXT 75
Visible Open-Out



APPLICATIONS 75 MM MODULE


OPEN-IN




Fixed frame



Bottom-hung




1 vent




2 vents




Turn/tilt or
tilt/turn 1 vent




Turn/tilt or tilt/turn
2 vents



Ribbon window




Fixed composite
open-in window




Fireman access



Residential door with
threshold 1 vent



Residential door with
threshold 2 vents



Juliet balcony

OPEN-OUT



Top-hung




Fixed composite
top-hung




Side hung
1 vent




Side hung
2 vents



Pivot
H + V



Residential door
with threshold
1 vent



Residential door
with threshold
2 vents



SOLEAL NEXT 65
Minimal Open-In



SOLEAL NEXT 65
Visible Open-In



APPLICATIONS 65 MM MODULE


OPEN-IN




Fixed frame



Bottom-hung




1 vent




2 vents




Turn/tilt or
tilt/turn 1 vent




Turn/tilt or tilt/turn
2 vents



Ribbon window




Fixed composite
open-in window




Fireman access



Residential door with
threshold 1 vent




Residential door with
threshold 2 vents




Juliet balcony


OPEN-OUT*




Top-hung



Fixed composite
top-hung




Side hung
1 vent




Side hung
2 vents



Pivot
H + V



Residential door
with threshold
1 vent



Residential door
with threshold
2 vents

* available in 2023.

SOLEAL NEXT

/ RESIDENTIAL DOOR

2 BOTTOM SECTION OPTIONS

- Features no threshold with drop seal
- One low threshold profile to allow easy entrance for disabled

ENDURANCE

- Door hinges tested: 200.000 cycles

APPLICATIONS



- Single and double residential door open-in
- Single and double residential door open-out



/ MORE ACCESSIBILITY

THRESHOLD FOR DISABLED

- Adapted for easy access on all available applications:
 - Easy opening / closing
 - Adaptable handle height
- No functional gasket at bottom
- No front drainage like flush doors
- Sloped < 5mm
- 15 mm and 20 mm solution can be used with support profile



SOLEAL NEXT


/ MORE COMFORT

JULIET GUARDING


Integrated into the window system, the Juliet guarding is a glass balustrade which provides additional safety for peace of mind.

- Can be fixed on 65 and 75 mm module
- Glass can be installed from the inside or from outside
- Limited to 35 mm protrusion for roller shutters
- End plugs without screws visible from the outside
- 2 profiles dimensions to allow standard or XL Juliet balcony
 - Standard glazing and max dimensions: 66,4 / 1300mm - 88,4 / 1600 mm. Maximum height 1200mm
 - XL glazing and max dimensions: 1010,4 / 2300mm - 1212,4 / 2900 mm. Maximum height 1200mm







Soleal Next 65: Fixation from the inside



Soleal Next 65: fixation from the outside



Soleal Next 75: Fixation from the inside



Soleal Next 75: fixation from the outside


SOLEAL NEXT

/ MORE COMFORT

MAGNETIC WINDOW CONTACT

The magnetic window contact is an additional security features as it sends an alert on the user's device when the window is not properly closed.

- Easy to mount
- Integrated into the profile
- Certified for high-end security



WIRELESS WINDOW CONTACT

The wireless window detects the opening and closing state of the window.

- Easy to install and pair
- Suitable for building management system: for EnOcean
- Compatible with many home automation boxes, including Tahoma box from Somfy
- HVAC management
- Designed in recycled ABS
- Energy harvesting (no battery)

MOTORISED OPENING CONTROL TO REDUCE ENERGY LOSS

Motorisation can be integrated in SOLEAL Next Minimal and Visible vent, tilt open-in, in both 65 and 75 modules.

- Simple solution, easy to install
- Concealed chain engine
- 1 or 2 chain drive depending on configuration
- High tightness performances: A4 - 900 Pa - C3
- Optional motorised window module available: provide feedback information, allows to control the motorisation in several ways and with other equipment
- Silent operation system; less than 35 dB
- Suitable for building management system : EnOcean and Modbus RTU
- 3 years guarantee



SOLEAL NEXT

/ MORE SAFETY

BURGLARY RESISTANCE

SOLEAL Next provides excellent protection against burglary, up to Resistance Class 3 (RC3) in accordance with EN-1627-30 and PAS24. It can be fitted with multi-point locks as an optional feature. Locking handles are available to increase security and reduce the risk of burglary.

APPLICATIONS

RC3 available for the following window type:

- Visible 1 vent turn and turn & tilt

RC2 available for the following window types:

- Fixed frame
- Visible and Minimal 1 vent turn
- Visible and Minimal 1 vent turn & tilt

PAS 24 available for the following window types:

- Side hung 1 vent and 2 vents and top hung friction hinges open-out
- 1 vent turn & tilt open-in, Visible and Minimal vents



Architect: Anne Demians

Photographer: Jean Pierre PORCHER et Martin ARGYROGLO


SOLEAL NEXT

/ HIGHER PERFORMANCE

Thanks to the property of our recycled aluminium, we are able to reduce the CO₂ footprint on stage A1 to A3 (raw material supply, transport and manufacturing).

SUSTAINABILITY PERFORMANCES (Results obtained with double glazing windows)					
Application	Dimensions L x H (mm)	Global Warming Potential /m ² (kg CO2 eq. / m ²)	Global Warming Potential element (kg CO2 eq. / m ²)	Surface (m ²)	Transparent area (m ²)
SOLEAL Next 65 Visible	1000 x 1400	58.70	82.21	1.40	1.07
SOLEAL Next 65 Minimal	1000 x 1400	62.50	87.46	1.40	1.13
SOLEAL Next 75 Visible	1000 x 1400	53.90	75.50	1.40	1.07
SOLEAL Next 75 Minimal	1000 x 1400	58.70	82.20	1.40	1.13
SOLEAL Next 75 Open-out	1000 x 1400	57.80	80.87	1.40	1.03

Our modular design allows to cover several thermal performance levels, from hot temperature regions to the coldest parts of the world.



THERMAL PERFORMANCES - SOLEAL NEXT 65 (results obtained with «T-Performance +» version)									
Application	Dimensions W x H (mm)	U _g	1.1	1.0	1.0	0.7	0.6	0.5	
		spacer	Warm Edge Swisspacer Ultimate						
		glazing	24 mm	24 mm	28 mm	36 mm	42 mm	48 mm	
SOLEAL NEXT Visible Open-In 65 mm									
window, 1 vent	1230 x 1480	U _{f moy} =	1.9 W/m².K						
		U _w =	1.4	1.3	1.3	1.1	0.98	0.90	
		S _w =	0.54	0.54	0.54	0.49	0.49	0.49	
		T _{Lw} =	0.37	0.37	0.37	0.35	0.35	0.35	
patio window, 1 vent	1230 x 2180	U _{f moy} =	1.9 W/m².K						
		U _w =	1.3	1.3	1.3	1.0	0.93	0.85	
		S _w =	0.56	0.56	0.56	0.51	0.51	0.51	
		T _{Lw} =	0.39	0.39	0.39	0.36	0.36	0.36	
window, 2 vents	1530 x 1480	U _{f moy} =	1.9 W/m².K						1.8
		U _w =	1.4	1.4	1.3	1.2	1.1	1.0	
		S _w =	0.49	0.49	0.49	0.45	0.45	0.45	
		T _{Lw} =	0.35	0.35	0.35	0.33	0.33	0.33	
patio window, 2 vents	1530 x 2180	U _{f moy} =	1.9 W/m².K						1.8
		U _w =	1.4	1.3	1.3	1.1	1.0	0.96	
		S _w =	0.51	0.51	0.51	0.47	0.47	0.47	
		T _{Lw} =	0.36	0.36	0.36	0.34	0.34	0.34	
SOLEAL NEXT Minimal Open-In 65 mm									
window, 1 vent	1230 x 1480	U _{f moy} =	2.0 W/m².K						
		U _w =	1.4	1.3	1.3	1.0	0.96	-	
		S _w =	0.56	0.56	0.56	0.52	0.52	-	
		T _{Lw} =	0.39	0.39	0.39	0.37	0.37	-	
patio window, 1 vent	1230 x 2180	U _{f moy} =	2.0 W/m².K						
		U _w =	1.4	1.4	1.3	1.1	1.1	-	
		S _w =	0.53	0.53	0.53	0.48	0.48	-	
		T _{Lw} =	0.37	0.37	0.37	0.35	0.35	-	

SOLEAL NEXT

/ HIGHER PERFORMANCE

THERMAL PERFORMANCES - SOLEAL NEXT 75 (results obtained with «T-Performance +» version)								
Application	Dimensions L x H (mm)w	U _g	1.1	1.0	1.0	0.7	0.6	0.5
		spacer	Warm Edge Swisspacer Ultimate					
		glazing	24 mm	24 mm	28 mm	36 mm	42 mm	48 mm
SOLEAL NEXT Visible Open-In 75 mm								
window, 1 vent	1230 x 1480	U _{f moy} =	1.4 W/m².K					
		U _w =	1.3	1.2	1.2	0.96	0.87	0.79
		S _w =	0.54	0.54	0.54	0.49	0.49	0.49
		T _{Lw} =	0.37	0.37	0.37	0.35	0.35	0.35
patio window, 1 vent	1230 x 2180	U _{f moy} =	1.4 W/m².K					
		U _w =	1.3	1.2	1.2	0.92	0.83	0.75
		S _w =	0.56	0.56	0.56	0.51	0.51	0.51
		T _{Lw} =	0.38	0.38	0.38	0.36	0.36	0.36
window, 2 vents	1530 x 1480	U _{f moy} =	1.4 W/m².K					
		U _w =	1.3	1.3	1.2	1.0	0.94	0.86
		S _w =	0.49	0.49	0.49	0.45	0.45	0.45
		T _{Lw} =	0.34	0.34	0.34	0.32	0.32	0.32
patio window, 2 vents	1530 x 2180	U _{f moy} =	1.4 W/m².K					
		U _w =	1.3	1.2	1.2	1.00	0.91	0.83
		S _w =	0.51	0.51	0.51	0.47	0.47	0.47
		T _{Lw} =	0.36	0.36	0.36	0.33	0.33	0.33
SOLEAL NEXT Visible Open-Out 75 mm								
window, 1 vent	1230 x 1480	U _{f moy} =	1.5 W/m².K					
		U _w =	1.3	1.2	1.2	0.99	0.91	0.83
		S _w =	0.52	0.52	0.52	0.47	0.47	0.47
		T _{Lw} =	0.36	0.36	0.36	0.34	0.34	0.34
patio window, 1 vent	1230 x 2180	U _{f moy} =	1.5 W/m².K					
		U _w =	1.3	1.2	1.2	0.96	0.87	0.79
		S _w =	0.54	0.54	0.54	0.50	0.50	0.50
		T _{Lw} =	0.37	0.37	0.37	0.35	0.35	0.35
window, 2 vents	1530 x 1480	U _{f moy} =	1.5 W/m².K					
		U _w =	1.3	1.3	1.3	1.1	0.99	0.91
		S _w =	0.47	0.47	0.47	0.43	0.43	0.43
		T _{Lw} =	0.33	0.33	0.33	0.31	0.31	0.31

THERMAL PERFORMANCES - SOLEAL NEXT 75 (results obtained with «T-Performance +» version)								
Application	Dimensions L x H (mm)	U _g	1.1	1.0	1.0	0.7	0.6	0.5
		spacer	Warm Edge Swisspacer Ultimate					
		glazing	24 mm	24 mm	28 mm	36 mm	42 mm	48 mm
SOLEAL NEXT Minimal Open-In 75 mm								
window, 1 vent	1230 x 1480	U _{f moy} =	1.6 W/m².K			1.5 W/m².K		
		U _w =	1.3	1.2	1.2	0.96	0.87	0.78
		S _w =	0.56	0.56	0.56	0.52	0.52	0.52
		T _{Lw} =	0.39	0.39	0.39	0.36	0.36	0.36
patio window, 1 vent	1230 x 2180	U _{f moy} =	1.6 W/m².K			1.5 W/m².K		
		U _w =	1.2	1.2	1.2	0.92	0.83	0.74
		S _w =	0.58	0.58	0.58	0.53	0.53	0.53
		T _{Lw} =	0.40	0.40	0.40	0.37	0.37	0.37
window, 2 vents	1530 x 1480	U _{f moy} =	1.6 W/m².K			1.5 W/m².K		
		U _w =	1.3	1.2	1.2	1.0	0.94	0.85
		S _w =	0.53	0.53	0.53	0.48	0.48	0.48
		T _{Lw} =	0.37	0.37	0.37	0.34	0.34	0.34
patio window, 2 vents	1530 x 2180	U _{f moy} =	1.6 W/m².K			1.5 W/m².K		
		U _w =	1.3	1.2	1.2	1.00	0.91	0.82
		S _w =	0.55	0.55	0.55	0.50	0.50	0.50
		T _{Lw} =	0.38	0.38	0.38	0.35	0.35	0.35

SOLEAL NEXT

/ HIGHER PERFORMANCE

WEATHER PERFORMANCES - SOLEAL NEXT 65

Application	W x H (mm)	Air tightness	Water tightness	Wind resistance
Visible Open-In, 1 vent turn&tilt	1394 x 3044	A4	1500	C5
Visible Open-In, 1 vent turn&tilt	1500 x 1700	A4	1500	C5
Visible Open-In, 1 vent turn&tilt	1500 x 2300	A4	1500	C5
Visible Open-in, 2 vents turn&tilt	2000 x 2300	A4	9A	C5
Minimal Open-In, 1 vent turn&tilt	1500 x 1700	A4	1050	C5
Minimal Open-In, 1 vent turn&tilt	1200 x 2300	A4	1050	C5
Minimal Open-In, 2 vent turn&tilt	1700 x 2300	A4	9A	C2
Motorization 1 chain drive, 1 vent tilt	1290 x 990	A4	9A	C3
Motorization 2 chain drives, 1 vent tilt	2490 x 890	A4	900	C3
Residential door Open-In 65 mm, 1 vent	1200 x 2300	A3	3A	C2

WEATHER PERFORMANCES - SOLEAL NEXT 75

Application	W x H (mm)	Air tightness	Water tightness	Wind resistance
Visible Open-In, 1 vent turn&tilt	1500 x 1700	A4	1500	C5
Visible Open-In, 2 vents, turn&tilt	2000 x 2300	A4	9A	C2
Visible Open-Out, 1 vent side-hung	884 x 1844	A4	1500	C5
Visible Open-Out, 2 vents side-hung	1730 x 1844	A4	1350	C5
Visible Open-Out, top-hung, friction stay	1844 x 1844	A4	1800	C5
Minimal Open-In, 1 vent turn&tilt	1500 x 1700	A4	1050	C5
Motorization 1 chain drive, 1 vent tilt	1290 x 990	A4	9A	C3
Motorization 2 chain drives, 1 vent tilt	2490 x 890	A4	900	C3
Residential door open-out, 1 vent	1200 x 2300	A3	3A	C2

ACOUSTIC PERFORMANCES - SOLEAL NEXT 65							
L x H (mm)	Glazing composition	Glazing			Window		
		Rw	RA	RA,tr	Rw	RA	RA,tr
Visible, 1 vent turn&tilt							
1230 x 1480	4/16/6	36	35	31	36	34	31
	44.2/20/66.2	49	47	43	45	44	40
	88.2Ac/20/66.2Ac	52	51	47	47	46	44
Visible, 2 vents turn&tilt							
1450 x 2180	4/16/6	36	35	31	35	34	30
	44.2/20/66.2	49	47	43	45	44	40
	88.2Ac/20/66.2Ac	52	51	47	46	45	42
Minimal, 1 vent turn&tilt							
1230 x 1480	4/16/6	45	44	40	44	43	39
	44.2/20/66.2	36	35	31	35	34	32
	88.2Ac/20/66.2Ac	49	47	43	46	45	41

ACOUSTIC PERFORMANCES - SOLEAL NEXT 75							
L x H (mm)	Glazing composition	Glazing			Window		
		Rw	RA	RA,tr	Rw	RA	RA,tr
Visible, 1 vent turn&tilt							
1230 x 1480	4/16/6	36	35	31	36	34	31
	44.2/20/66.2	49	47	43	47	46	42
	88.2Ac/20/66.2Ac	52	51	47	48	47	45
Visible, Residential door							
1450 x 2180	4/16/6	36	35	31	35	33	30
	44.2/20/66.2	49	47	43	47	45	41
	88.2Ac/20/66.2Ac	52	51	47	47	45	42
Visible, 2 vents turn&tilt							
1230 x 1480	4/16/6	36	35	31	36	34	30
	10/16/66.2Ac	45	44	40	44	42	38
	44.2Ac/20/66.2Ac	49	47	43	46	44	40
Minimal, 1 vent turn&tilt							
1230 x 1480	10/16/66.2Ac	45	44	40	44	43	40
	66.2Ac/12/6/12/44.2Ac	49	47	43	47	46	42
	88.2Ac/20/66.2Ac	52	51	47	48	47	45

SOLEAL NEXT

/ COMMITMENT TO SUSTAINABILITY

TECHNAL demonstrates its strong commitment to the environment in all areas: by using recycled and low-carbon materials, with a product design that is adapted to a circular economy, and produced within a responsible supply chain. In addition, these statements are certified by external organisations to ensure maximum transparency.

HYDRO CIRCAL®

We are demonstrating our focus on sustainability by using Hydro CIRCAL® for our system solutions, one of the most sustainable aluminium alloys in our sector. Hydro CIRCAL® is a range of prime quality aluminium made with a minimum of 75% recycled end-of-life aluminium (post-consumer scrap). The production process is verified by an independent third party (DNV-GL), and confirmed by an EPD (Environmental Product Declaration). Hydro CIRCAL® also has **one of the smallest CO₂ footprint worldwide: 1.9 kg CO₂ per kilo of aluminium** – 4.5 times less than the world global primary average.

RECYCLED & RECYCLABLE

Following our path to the certified circular economy, all of our systems are composed with a majority of materials and components that can be infinitely recyclable, that can come from recycled raw materials, that can be recycled to have a second life or components that can also be reused.

In rough figures, we're talking about **75% recycled content and 95% recyclable content**. It's an efficient way to drastically reduce the impact of materials on the life cycle of a building. Finally, our greener approach goes a step further thanks to recycled thermal strips for 75 mm modules.



75%

**RECYCLED
POST
CONSUMER**

Hydro CIRCAL® is the world's first certified recycled aluminium which means that at least 75% of the prime-quality aluminium alloy comes from post-consumer materials.



95%

**ENERGY
SAVED**

By recycling post-consumer scrap aluminium, the remelting process saves up to 95% of energy that would normally be spent and maintain the same high quality as primary aluminium.



85%

**REDUCTION
OF CO₂
EMISSIONS**

The consequence of using Hydro CIRCAL® is the drastic reduction in CO₂ emissions which sums more than 85% when compared with the global average for primary aluminium production.

SOLEAL NEXT

75% RECYCLED

95% RECYCLABLE



SOLEAL NEXT

/ CERTIFICATIONS



CRADLE TO CRADLE (C2C) CERTIFICATION

From its design to the selection of materials and how it is manufactured, the product must offer the level of performance required by the market by reducing, to the greatest extent possible, environmental impacts such as energy consumption or greenhouse gas emissions.

We classify our range under the criteria of the Cradle to Cradle seal, an independent institute that certifies products and processes from a circular economy perspective. We have numerous Cradle to Cradle certified series, including the manufacturing in our plants. In this way, we are able to ensure that the carbon footprint of transporting our products is as low as possible.

Our range is under certification.



ALUMINIUM STEWARD INITIATIVE (ASI)

ASI is a multi-stakeholder, non-profit, standards-setting and certification organisation. It is the most internationally recognised standard, which addresses the environmental, social and governance (ESG) aspects of the entire aluminium value chain. The assessment is based around the sustainable production of aluminium, from bauxite or mining to the production of semi-fabricated products, taking into account the recycling of pre- and post-consumer scrap. Hydro was one of the first companies, that received this recognition, in accordance with its commitment to a more sustainable future.

100% of our extrusion plants are ASI Performance Standard Certified.



ENVIRONMENTAL PRODUCT DECLARATION

An Environmental Product Declaration (EPD) is an independently third party-verified document that communicates precise, transparent and comparable information about the life-cycle environmental impacts of a product. But it is not only limited to products, such as a window, but can also be applied to materials (an aluminium billet), assembly parts of products or even for services (like maintenance). This document is used for many different applications, e.g. public procurement or green building rating schemes (i.e. BREEAM, LEED, DGNB).

Thanks to our software TechDesign, it's possible to generate a dynamic EPD according specified dimensions, applications any type of glazing.





IMAGINE WHAT'S NEXT

Head Office
Severn Drive, Tewkesbury
Gloucestershire
GL20 8SF

Tel +44 1684 853500

Northern Office
Cedar Court Office Park,
Denby Dale Road, Wakefield
WF4 3FU

info.uk@hydro.com

London Office
The Building Centre
26 Store Street, London
WC1E 7BT

www.technal.co.uk

